550

SILICON LUBRICANT



SAFETY DATA SHEET AVAILABLE ON REQUEST

Always refer to the descriptions on labels. Keep out of reach of children. Respect the conditions of use.

Description

- Colorless multi-purpose silicone water-repellent grease, resistant to infiltrations.
- It makes a good insulator for electrical contacts, and does not stain.
- For all moving parts, electrical contacts and all parts to be protected.

Product information

Composition	EC 927-510-4 HYDROCARBONS, C7, N ALKANES, isoalkanes, Cyclics EC 931-254-9 HYDROCARBONS, C6, isoalkanes, <5% N-hexane
Appearance/ Odour	Liquid / odorless
pH	N.A
Density	<1
Flash point	N.A
Transport N° ONU	1950
Storage	Store between + 5 ° C. and + 30 ° C. in a dry, well ventilated place, away from sources of ignition.
Packaging	200ml aerosol

Directions for use

Compatibility / supports	Electrical contacts, hinges, slides , tools, locks, etc.
Méthodes	- Always shake before use. - Spray at approximately 20cm from the previously cleaned elements to be greased. - Always purge the can head down for a few seconds after use to clean the spray nozzle.

Precautions for use



- Extremely flammable aerosol. Pressurized container: May burst if heated.

Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.
Before use: Shake the can. Always carry out a test on a small surface.
This spray can be used in multi-positions, head up - upside down.

Made in France by Proyacht SARL
460, Av. de la Quiera - 213 Voie E - 06370 Mouans-Sartoux
Tél. : +33 (0) 493 229 865
Clin'Azur & Proyacht are registered trademarks